

The logo consists of the letters 'LA-SO'. The 'LA' is in a black sans-serif font, while the 'SO' is in a red sans-serif font. The 'O' in 'SO' is a hollow circle.

051790



Economical and flexible Swing-On Applicator

Advantages of the Label-Applicator Swing-On:

- Application of labels on products ranging from individual items to multiple boxes
- Plug & play integration with ALX 92x Print & Apply
- High output for top, side or leading edge application to products
- Complete solution for printing and labelling within the logistics industry
- Durable industrial design for reliable operation
- Applies labels to moving products
- Low maintenance with less wearing parts



Monarch®
Products and Services

Your LA-SO at a glance

Label stock:	
Type of label stock:	Self adhesive material (paper, film*)
Material width:	80 - 150 mm
Material length:	80 - 210 mm

* Due to static and friction effects, film materials may tend to wrinkle during dispense of the label onto the vacuum pad. Film materials are subject to be tested upfront in your unique application.

Capacity:	
Capacity LA-SO on ALX 92x:	Capacity depends mainly upon the following factors - label-size, material-length, print-speed, conveyor-/product-speed, product-length, product-distance and position of the label to the product.

Apply specifications:	
Apply tolerance:	+/- 2 mm
Apply direction to product:	Top positioning: leading edge or top Side positioning: leading edge or side
Apply distance:	To leading edge of product: approx. 100 mm To top or side of product: approx. 200mm
Product speed at application:	Up to max. 15 m/min at leading edge application Up to max. 30 m/min at top or side application
Air stream:	By ventilator

Connection:	
Power supply:	By means of Applicator Interface Board
Power consumption:	15 VA
Air supply:	4 - 6 bar
Air consumption:	0.3 litre per stroke

Dimensions:	
W x H x D ALS:	240 x 355 x 500 mm
Weight:	Approx. 6.5 kg

Environmental data:	
Operating temp.:	5 - 40° C
Storage temp.:	0 - 70° C
Humidity:	30 - 80 % non condensing
Noise:	< 75 dB (A)
Protection class:	IP 21
Safety requirement:	CE

You're never far from an Avery Dennison representative:	Benelux Denmark / Scandinavia France Germany	Iberia India Italy	Poland PR China / Hong Kong Turkey	UAE UK USA
--	---	--------------------------	--	------------------

Avery Dennison Deutschland GmbH
Ohmstrasse 3, D-85386 Eching
Phone: +49/(0) 81 65/925 - 299
Fax: +49/(0) 81 65/6 43 60
printers@eu.averydennison.com
www.machines.averydennison.com

