

CHAINWAY C2000

Handheld Data Terminal



FEATURES

- **Very Portable Design**
- **Familiar Windows CE**
- **Essential Barcode Scan**
- **Popular RFID Tech.**
- **Wireless Communications**
- **Water/Dust Proof IP54**
- **Drop survival 1.2m/3.9ft.**
- **Clear LCD display**
- **C#, C++, VB.NET**

CHAINWAY C2000 handheld data terminal was marked with compact size, portability, durability, functionality and flexibility, which is customized for enterprise administrative personnel and mobile staff, as well as business application and IT demands.

A set of advanced data capture module in various business fields can obtain abundant and accurate data automatically, matching the verified module with responsive staff. You can now choose either 1D laser scanner with highest performance or 2D imager scanner capable of collecting 1D/2D barcodes to meet the high demand for barcode scanning. And add the 3.2 mega pixels camera to capture any necessary photograph at

site. It abides by design philosophy of portability and good-looking industrial design, compact size and ease of use, waterproof and dustproof, sturdiness and durability, high precision, high speed, extensibility and customization to meet different industrial data capture.

CHAINWAY C2000 adopts industrial standard, a great amount of mobile solutions can be achieved with this device. Workers can enjoy a convenient and light-hearted working state with this model. The reduced deployment complexity greatly saves the operational cost, as well as significantly improves the work efficiency. For that, CHAINWAY C2000 can bring you the greatest return on investment.

Handheld Data Terminal C2000



1D Barcode



2D Barcode



RFID



GPRS



Camera



Bluetooth



Wi-Fi

Accessories

Standard



AC adapter



USB cable



Stylus Passive



Rechargeable Battery

Optional



Single unit charger



carrying case

PHYSICAL CHARACTERISTICS

Dimension	148 × 71 × 31mm / 5.83 × 2.80 × 1.22in.
Weight	280g / 9.88oz. (includes battery)
Display	2.8"QVGA TFT-LCD touch screen with backlight, 240 × 320 resolution, 65K colors
Keypad	Numeric
Battery	Rechargeable Li-ion polymer battery 3200mAh
Expansion slot	SIM, MicroSD (TF)
Audio	0.5Watt speaker
Interfaces	USB2.0 Device

PERFORMANCE CHARACTERISTICS

CPU	Samsung ARM920T@533MHz
RAM	128MB
Storage	1GB Flash, MicroSD (Max.32GB expansion)

PROGRAMMING ENVIRONMENT

Operating System	Windows Embedded CE6.0 Core Windows Embedded CE6.0 Pro (Optional)
SDK	Chainway software development kit
Language	C#, C++, VB.NET
Tool	Microsoft Visual Studio 2005/2008

USER ENVIRONMENT

Operating Temp.	-20 to 50°C / -4 to 122°F
Storage Temp.	-25 to 70°C / -13 to 158°F
Humidity	5% - 95%RH (Non-condensing)
Tumble Spec	1,000 0.5m tumbles
Sealing	IP54, IEC Compliance
Drop Spec.	1.2m / 3.9ft. drop to concrete, 6 drops per 6 sides over operating temperature range

CAMERA (OPTIONAL)

Samsung 3.2MP camera 2048(H)×1536(V), QXGA

BARCODE SCANNER

1D Linear Scanner	
1D Laser/CCD	Symbol SE955 / SE655
Symbologies	All major 1D barcodes
2D Imager Scanner	
2D CMOS laser scanner	Symbol SE4500
Symbologies	PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, A ztec, MaxiCode; Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal, Dutch Postal (KIX), etc.

RFID READER

Frequency	13.56MHz
Protocol	ISO14443A/B, ISO15693
Chips	1) M1(S50/S70), M0(Ultralight), M3(Desfire D40/D41/D81), CPU_A 2) CPU_B 3) ICODE II, Ti2048, LRI64K 4) Others for customization
R/W range	2 - 10cm / 0.79 - 3.94in.

WWAN

GPRS 900/1800MHz or 850/900/1800/1900MHz

WPAN

Bluetooth v2.0+EDR, range 5 - 10m / 16.40 - 32.80ft.

WLAN

Wi-Fi IEEE802.11b/g

Shenzhen Chainway Information Technology Co., Ltd.

Add: 9/F, Building 2, Phase 2, Gaoxinqi Industrial Park, Liuxian 1st Rd., District 67, Bao'an, Shenzhen, Guangdong 518102, China
0086-755-23223316 Fax:0086-755-23223310 sales@chainway.cn http://www.chainway.net

