



M100 Series



M300 Series



M200 Series

M-SERIES CAMERAS

M-Series cameras enable fast integration of challenging machine vision solutions. The unique ability to mix and match color, gray-scale, multi imager, area and line scan cameras with an MX-Series processor lets you define, select and deploy the perfect imaging solution for high-speed, multi-camera machine vision inspections.

HIGHLIGHTS

- GigE compatible for easy communication to M-Series processor
- VGA to 5MP resolution, in both gray scale and color
- Camera settings fully controllable by Impact Software
- Power over Ethernet (PoE) reduces cabling complexity
- Small form factor (as little as 29 mm x 29 mm x 60 mm) enables mounting in space-constrained locations
- Asynchronous triggering enables each camera to independently capture images at rates up to 210 frames per second (fps)
- Trigger and strobe I/O on camera eases integration

TECHNICAL SPECIFICATIONS

MX-SERIES GIG-E CAMERAS

	GRAY-SCALE MODEL	COLOR MODEL	SHUTTER	RESOLUTION	IMAGER	FRAME RATE (FPS)	DIMENSIONS
	M100	M100C	Global	640 x 480	1/4" CCD	100	29 x 29 x 60.3 mm (1.14 x 1.14 x 2.37 in)
	M110	M110C	Global	640 x 480	1/3" CCD	90	
	M115	M115C	Global	659 x 494	1/2" CCD	100	
	M125	M125C	Global	782 x 582	1/2" CCD	75	
	M150	M150C	Global	1296 x 966	1/3" CCD	30	
	M180	M180C	Global	1628 x 1236	1/1.8" CCD	20	
	M190	M190C	Global	2048 x 1088	2/3" CMOS	50	
	M195	M195C	Global	2048 x 2048	1" CMOS	25	
	M197	M197C	Rolling	2592 x 1944	1/2.5" CMOS	14	
	M200	M200C	Global	659 x 494	1/3" CCD	70	44 x 29 x 85.5 mm (1.73 x 1.14 x 3.37 in)
	M202	M202C	Global	659 x 494	1/2" CCD	79	
	M205	M205C	Global	752 x 480	1/3" CMOS	64	
	M210	M210C	Global	782 x 582	1/2" CCD	55	
	M230	M230C	Global	1034 x 779	1/3" CCD	31	
	M250	M250C	Global	1280 x 960	1/3" CCD	32	
	M270	M270C	Global	1392 x 1040	2/3" CCD	30	
	M290	M290C	Global	1628 x 1236	1/1.8" CCD	14	
	M295	M295C	Global	1628 x 1236	1/1.8" CCD	28	
	M300	M300C	Global	648 x 488	1/3" CCD	210	44 x 29 x 98.5 mm (1.73 x 1.14 x 3.88 in)
	M330	M330C	Global	1004 x 1004	2/3" CCD	60	
	M350	M350C	Global	1608 x 1208	1" CCD	35	
	M390	M390C	Global	2448 x 2050	2/3" CCD	17	

BENEFITS

- GigE compatible for fast integration with M-Series processors
- Compact size fits many machine configurations
- High-speed trigger input
- High-speed strobe light output
- C-mount lens support
- IP30 rated housing
- CE, FCC and RoHS compliant
- Utilizes color inspection tools

Rev. 00, 02/2014

The company endeavours to continuously improve and renew its products; for this reason the technical data and contents of this catalogue may undergo variations without prior notice. For correct installation and use, the company can guarantee only the data indicated in the instruction manual supplied with the products. Product and Company names and logos referenced may be either trademarks or registered trademarks of their respective companies. We reserve the right to make modifications and improvements.

www.datalogic.com