

	model	PR-C101	PR5300	PR5310	PR5350
1	resolution	300dpi	300dpi	300dpi	300dpi
2	tone	256	256	256	256
3	printing area	edge to edge	edge to edge	edge to edge	edge to edge
4	printing speed (S/print)	25(3BP)	45(YMCKO)	45(YMCKO)	28(3BP)
5	both sides	N/A	Yes	Yes	Yes
6	capacity of cards feed (0.76)	100	100	100	100
7	capacity of cards ejection (0.76)	30	100	100	100
8	thickness of card (mil)	30	20 to 50	20 to 50	20 to 50
9	number of ribbon printing sheets/Roll	250(YMCKO) 500(KO)	250(YMCKO) 210(YMCKOK)	250(YMCKO) 210(YMCKOK)	250(3BP) 210(YMCKOK)
10	card size	CR-80	CR-80	CR-80	CR-80
11	I/F	USB	USB Ethernet	USB Ethernet	USB Ethernet
12	equipment size (WxDxH)	270x331x421	270x331x421	270x331x421	270x331x421
13	equipment weight (kg)	6.5	13	13	13
14	Extende image and function memory	8	8	8	16
15	Separate memory mode	N/A	5	5	5
16	Card input/output hopper	100/30	100/100	100/100	100/100
17	magnetic encode	PR-C101M	Option	Option	Option
18	contact IC	N/A	N/A	Option	Option
19	contactless IC	future option	N/A	Option	Option
20	appearance				